



MATERIAL SAFETY DATA SHEET

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Multi-Purpose Lubricator and Penetrating Oil (Aerosol)
Product Number: HMP051, HMP053, HMP055, HMP056
Product Use: Petroleum lubricant.
Manufacturer/Supplier: R.B. Howes & Co., Inc. / Howes Lubricator
60 Ocean State Drive
North Kingstown, RI
Phone Number: 1-401-294-5500, 1-800 GET HOWES (438-4693)
Emergency Phone: CHEMTREC: 1-800-424-9300
Date of Preparation: June 1, 2015

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER

EXTREMELY FLAMMABLE. HARMFUL BY INHALATION. MAY CAUSE EYE IRRITATION. IRRITATING TO SKIN. CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED. MAY CAUSE CANCER. MAY CAUSE TERATOGENICITY AND EMBRYOTOXICITY.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.
Skin: Irritating to skin.
Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.
Inhalation: Harmful by inhalation. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness. This product may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Contains ingredients known or suspected to be carcinogenic, teratogenic and/or embryotoxic.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	40 - 70
Stoddard solvent	8052-41-3	15 - 40
Distillates (petroleum), hydrotreated light	64742-47-8	10 - 30
Carbon dioxide	124-38-9	1 - 5



MATERIAL SAFETY DATA SHEET

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

Bis (dinonylnaphthalenesulphonate) barium	25619-56-1	1 - 5
Nonane	111-84-2	1 - 5
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Pine oil	8002-09-3	1 - 5
Methyl salicylate	119-36-8	0.1 - 1
Naphthalene	91-20-3	0.1 - 1
Xylene	1330-20-7	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention or call poison control immediately.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Flammable by WHMIS criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, foam, carbon dioxide, water fog.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Use water spray to keep fire-exposed containers cool. In case of fire and/or explosion do not breathe fumes. Vapours can flow to distant ignition sources and flash back. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container. Provide ventilation.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle container with care. Follow proper bonding and grounding procedures. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep locked up and out of reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49 °C / 120 °F. Store away from direct sunlight or other heat sources.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits ACGIH-TLV
Distillates (petroleum), hydrotreated heavy naphthenic	Not available.
Stoddard solvent	100 ppm
Distillates (petroleum), hydrotreated light	Not available.
Carbon dioxide	5000 ppm
Bis (dinonylnaphthalenesulphonate) barium	Not available.
Nonane	200 ppm
1,2,4-Trimethylbenzene	Not available.
Pine oil	Not available.
Methyl salicylate	Not available.
Naphthalene	10 ppm
Xylene	100 ppm
Ethylbenzene	20 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Not available.
Colour:	Dark amber.
Odour:	Distinctive.
Odour Threshold:	Not available.
Physical State:	Gas/Pressurized Liquid.



MATERIAL SAFETY DATA SHEET

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

pH:	Not available.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	164 °C (327 °F)
Flash Point:	65.6 °C (150 °F) Rapid Flash Point Closed-Cup, ASTM D3243 (Liquid)
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	< 0.1 mm Hg
Vapor Density:	> 1 (Air = 1)
Specific Gravity:	< 0.9
Solubility in Water:	Insoluble.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	461 g/L

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials. Sources of ignition.

Incompatible Materials: Strong oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC₅₀
Distillates (petroleum), hydrotreated heavy naphthenic	> 5000 mg/kg, rat	> 5.0 mg/L 4hr, rat
Stoddard solvent	Not available.	Not available.
Distillates (petroleum), hydrotreated light	> 5000 mg/kg, rat	> 5.2 mg/L 4hr, rat
Carbon dioxide	Not available.	Not available.
Bis (dinonylnaphthalenesulphonate) barium	1750 mg/kg, rat	>21 mg/l/1h, rat
Nonane	Not available.	3200 ppm 4hr, rat
1,2,4-Trimethylbenzene	3280 mg/kg, rat	18000 mg/m ³ 4hr, rat
Pine oil	3200 mg/kg, rat	Not available.
Methyl salicylate	887 mg/kg, rat	Not available.
Naphthalene	490 mg/kg, rat	> 340 mg/m ³ 1hr, rat;
Xylene	4300 mg/kg, rat	> 0.4 mg/L 4hr, rat
Ethylbenzene	3500 mg/kg, rat	5000 ppm 4hr, rat
		17.2 mg/L 4hr, rat

MATERIAL SAFETY DATA SHEET
Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

- Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Skin:** Irritating to skin. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting. Harmful: may cause lung damage if swallowed.
- Inhalation:** Harmful by inhalation. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness. This product may be aspirated into the lungs and cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE

- Target Organs:** Not available.
- Chronic Effects:** Not hazardous by WHMIS criteria.
- Carcinogenicity:** Hazardous by WHMIS criteria.

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Distillates (petroleum), hydrotreated heavy naphthenic	Not listed.
Stoddard solvent	Not listed.
Distillates (petroleum), hydrotreated light	Not listed.
Carbon dioxide	Not listed.
Bis (dinonylnaphthalenesulphonate) barium	Not listed.
Nonane	Not listed.
1,2,4-Trimethylbenzene	Not listed.
Pine oil	Not listed.
Methyl salicylate	Not listed.
Naphthalene	G-A3, I-2B, N-2
Xylene	G-A4, I-3
Ethylbenzene	G-A3, I-2B

* See Section 15 for more information.

- Mutagenicity:** Not hazardous by WHMIS criteria.
- Reproductive Effects:** Not hazardous by WHMIS criteria.
- Developmental Effects:**
- Teratogenicity:** Hazardous by WHMIS criteria.
 - Embryotoxicity:** Hazardous by WHMIS criteria.
- Respiratory Sensitization:** Not hazardous by WHMIS criteria.
- Skin Sensitization:** Not hazardous by WHMIS criteria.
- Toxicologically Synergistic Materials:** Not available.

Section 12: ECOLOGICAL INFORMATION

- Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.
- Persistence / Degradability:** Not available.
- Bioaccumulation / Accumulation:** Not available.
- Mobility in Environment:** Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

TDG Classification

UN1950, Aerosols, flammable, Class 2.1
Limited Quantity (≤ 1L)

Section 15: REGULATORY INFORMATION

Federal Regulations

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Global Inventories

Ingredient

**Canada
DSL/NDSL**

Distillates (petroleum), hydrotreated heavy naphthenic	DSL
Stoddard solvent	DSL
Distillates (petroleum), hydrotreated light	DSL
Carbon dioxide	DSL
Bis (dinonylnaphthalenesulphonate) barium	DSL
Nonane	DSL
1,2,4-Trimethylbenzene	DSL
Pine oil	DSL
Methyl salicylate	DSL
Naphthalene	DSL
Xylene	DSL
Ethylbenzene	DSL

HMIS - Hazardous Materials Identification System

Health - 2* Flammability - 4 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 4 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

- Class A - Compressed Gas
- Class B5 - Flammable Aerosol
- Class D2A - Carcinogenicity
- Class D2A - Teratogenicity and Embryotoxicity
- Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:





MATERIAL SAFETY DATA SHEET

Multi-Purpose Lubricator and Penetrating Oil (Aerosol)

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: June 1, 2018

Version #: 1.0

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com