

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 Date of issue: 06/01/2015 Revision date: 06/01/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Winter Treat Plus Product name Product code 103051, 103052, 103073

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Motor Fuel Additive

Details of the supplier of the safety data sheet

R.B. Howes & Co., Inc. / Howes Lubricator 60 Ocean State Drive North Kingstown, RI

T 401-294-5500, 1-800 GET HOWES (438-4693)

Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Flammable Liquid 3

Skin Irritation 2

Eye Irritation 2A

Carcinogenicity 2

Specific target organ toxicity - Repeated exposure 1

Aspiration Toxicity 1

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)





GHS07

GHS08

Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US)

Keep away from heat/sparks/open flames/hot surfaces.- No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/ gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. If exposed or concerned: Get medical advice/attention. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available.

Unknown acute toxicity (GHS-US)

34 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

06/01/2015 EN (English) Page 1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates, petroleum, hydrotreated middle	(CAS No) 64742-46-7	15 - 40	Flam. Liq. 4 Acute Tox. 4 (Inhalation) Asp. Tox. 1
Stoddard solvent	(CAS No) 8052-41-3	15 – 40	Skin Irrit. 2 STOT RE 1 Asp. Tox. 1
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	10 – 30	Flam. Liq. 3 Asp. Tox. 1
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	7 – 13	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A Asp. Tox. 1
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	7 – 13	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	1 – 5	Flam. Liq. 3 Asp. Tox. 1
Fatty acid amine reaction product	Trade secret	1 – 5	Skin Irrit. 2 Eye Irrit. 2A
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 – 5	Flam. Liq. 3 Acute Tox. 4 (Dermal) Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A
1,3,5-Trimethylbenzene	(CAS No) 108-67-8	1 – 5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A STOT SE 3 Asp. Tox. 1
1,2,3-Trimethylbenzene	(CAS No) 526-73-8	1 - 5	Flam. Liq. 3 Skin Irrit. 2 Eye Irrit. 2A STOT SE 3
Nonane	(CAS No) 111-84-2	1 – 5	Flam. Liq. 3 Acute Tox. 4 (Inhalation) Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Naphthalene	(CAS No) 91-20-3	0.5 - 1.5	Acute Tox. 4 (Oral) Carc. 2
Ethylbenzene	(CAS No) 100-41-4	0.1 - 1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Skin Irrit. 2 Eye Irrit. 2B Carc. 2 Asp. Tox. 1
Cumene	(CAS No) 98-82-8	< 0.1	Flam. Liq. 3 Carc. 2 STOT SE 3 Asp. Tox. 1

^{*} The specific chemical identity and exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

First-aid measures after eye contact

First-aid measures after ingestion

4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

: If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

06/01/2015 EN (English) 2/1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking

of the skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and

cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Powder, water fog, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA). Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to

unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2. Methods and material for containment and cleaning up

For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable

container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal

Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Spilled material may present a slipping

hazard. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Do not

breathe dust/fume/gas/mist/vapors/ spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep locked up and out of reach of children. Keep container tightly closed and in a well-

ventilated place. Keep cool.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates, petroleum, hydrotreated middle (64742-46-7)	
ACGIH	Not applicable
OSHA	Not applicable

Stoddard solvent (8052-41-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	2900 mg/m³



Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Stoddard solvent (8052-41-3)		
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Detroloum distillates budget	rested light (C4742 47 0)	
Petroleum distillates, hydrotreated light (64742-47-8) ACGIH Not applicable		
OSHA	Not applicable	
OOLIA	Not applicable	
Solvent naphtha, petroleum,		
ACGIH	Not applicable	
OSHA	Not applicable	
Benzene, 1,2,4-trimethyl- (95	-63-6)	
ACGIH	Not applicable	
OSHA	Not applicable	
Solvent naphtha, petroleum,	heavy aromatic (64742-94-5)	
ACGIH	Not applicable	
OSHA	Not applicable	
Fatty acid amine reaction pro	Not applicable	
OSHA	Not applicable	
OSHA	Not applicable	
Xylenes (o-, m-, p- isomers)	•	
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
1,3,5-Trimethylbenzene (108-	67-8)	
ACGIH	ACGIH TWA (ppm)	25 ppm
OSHA	Not applicable	
1,2,3-Trimethylbenzene (526-	.72.2\	
ACGIH	Not applicable	
OSHA	Not applicable	
Nonane (111-84-2) ACGIH	ACGIH TWA (ppm)	200 ppm
	" ' /	200 ррті
OSHA	Not applicable	
Naphthalene (91-20-3)		
ACGIH	ACGIH TWA (ppm)	10 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	10 ppm
Ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
		_ · · · · · · · · · · · · · · · · · · ·





Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Cumene (98-82-8)		
OSHA	OSHA PEL (TWA) (ppm)	50 ppm

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear eye protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : No data available
Colour : Light amber
Odour : Distinctive
Odour threshold : No data available
pH : No data available

Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Flash point : 54.4 °C (130 °F)
Relative evaporation rate (butylacetate=1) : No data available
Flammability (solid, gas) : Flammable
Explosive limits : No data available

Explosive properties : No data available

Oxidising properties : No data available

Vapour pressure : < 0.1 mm Hg

Relative density : < 0.9 (H2O = 1)

Relative vapour density at 20 °C : > 1 (air = 1)

Solubility : Insoluble.

Partition coefficient: n-octanol/water : No data available

Log Kow : No data available

Log Kow: No data availableAuto-ignition temperature: No data availableDecomposition temperature: No data availableViscosity: No data available

Viscosity, kinematic : < 20.5 cSt @ 40 °C (104 °F)

Viscosity, dynamic : No data available

9.2. Other information

VOC content : 715 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

06/01/2015 EN (English) 5/1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Strong oxidizers.

Nonane (111-84-2) LC50 inhalation rat

LD50 dermal rabbit

LD50 oral rat

Naphthalene (91-20-3)

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

Winter Treat Plus		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
LC50 inhalation rat	Not available.	
Distillates, petroleum, hydrotreated middle (6	4742-46-7)	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	4.6 mg/l/4h	
Petroleum distillates, hydrotreated light (6474	12-47-8)	
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	> 5.2 mg/l/4h	
Solvent naphtha, petroleum, light aromatic (6	4742-95-6)	
LD50 oral rat	8400 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	3400 ppm/4h	
Benzene, 1,2,4-trimethyl- (95-63-6)		
LD50 oral rat	3280 mg/kg	
LD50 dermal rabbit	> 3160 mg/kg	
LC50 inhalation rat	18 g/m³/4h	
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2 ml/kg	
LC50 inhalation rat	> 5.28 mg/l/4h	
Fatty acid amine reaction product		
LD50 oral rat	> 3000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
LD50 oral rat	4300 mg/kg	
LD50 dermal rabbit	1700 mg/kg	
LC50 inhalation rat	5000 ppm/4h	
1,3,5-Trimethylbenzene (108-67-8)		
LC50 inhalation rat	24 g/m³/4h	

 Ethylbenzene (100-41-4)

 LD50 oral rat
 3500 mg/kg

 LD50 dermal rabbit
 15400 mg/kg

3200 ppm/4h

490 mg/kg

>20 g/kg

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Ethylbenzene (100-41-4)		
LC50 inhalation rat	17.2 mg/l/4h	
Cumene (98-82-8)		
LD50 dermal rabbit	12300 μL/kg	
LC50 inhalation rat	>3577 ppm/6h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.	
Carcinogenicity	: Suspected of causing cancer.	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
IARC group	3 - Not classifiable	
Naphthalene (91-20-3)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen	
Ethylbenzene (100-41-4)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity	
Cumene (98-82-8)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen	
Reproductive toxicity	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Symptoms/injuries after inhalation	: May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.	
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.	
Symptoms/injuries after eye contact	: Causes serious eye irritation; Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.	
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.	

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Winter Treat Plus	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Winter Treat Plus	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Additional information : Handle empty containers with care because residual vapours are flammable.





Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

UN-No.(DOT) : UN1268

Proper Shipping Name (DOT) : Petroleum distillates, n.o.s.

Transport hazard class(es) (DOT) : 3

Hazard labels (DOT)

3

Packing group (DOT) : III

Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Nonane (111-84-2)	

Nonane (111-84-2)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
Xvlenes (o-, m-, p- isomers) (1330-20-7)		

Aylenes (0-, m-, p- isomers) (1330-20-7)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %

Naphthalene (91-20-3)	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	0.1 %

Ethylbenzene (100-41-4)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %

15.2. US State regulations

Winter Treat Plus	
State or local regulations	This product contains chemicals known to the State of California to cause cancer.

SECTION 16: Other information

Date of issue : 06/01/2015 Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

